

# W. R. MEADOWS®, INC.

P.O. BOX 338  
HAMPSHIRE, IL 60140-0338  
TELEPHONE: (847) 214-2100 • TELEFAX: (847) 683-1338

**FOR ADDITIONAL INFORMATION CONTACT**  
Ashley Gee (847) 214-2100

## FOR IMMEDIATE RELEASE

### HS-1 SL FOR MOVEMENT AND CONNECTION JOINTS

**Hampshire, IL** – HS-1 SL self-leveling hybrid sealant developed with silyl-modified polymer (SMP) technology cures under the influence of atmospheric moisture. HS-1 SL's one-part formulation eliminates mixing and convenient 32 oz. size makes it easy to handle. HS-1 SL is applied directly from its packaging and can be resealed. No tooling or caulking gun is required.

HS-1 SL can be used in movement and construction joints and is ideal for sidewalks and driveways subject to pedestrian traffic. HS-1 SL adheres to green concrete, damp surfaces, and most construction materials. HS-1 SL is available in gray and tan to best match the application site.

"HS-1 SL has become a fan favorite very quickly. The easy-to-use pouch eliminates the need for a caulking gun that is required when using cartridges. The 32-oz. pouch comfortably fits in your hand for easy application. This new, innovative pouch really makes a difference in the ease of application. The sealant offers excellent expansion capabilities and resistance to chlorine and salt water," said Jim Dill, Division Manager.

Further information about HS-1 SL can be found at <https://www.wrmeadows.com/hs1-sl-one-part-self-leveling-smp-based-sealant/>.

###